



675SR-R

RACING TRIPLE



> POWER

| | |
|-------------------|--|
| Engine | 3-cylinder, inline 4-stroke, liquid-cooled, DOHC |
| Displacement | 675cc |
| Bore x Stroke | 72x55.2 mm |
| Maximum Power | 70kW/11,000rpm |
| Maximum Torque | 70Nm/8,250 rpm |
| Fuel System | BOSCH EFI |
| Compression Ratio | 11.5:1 |
| Transmission | CF-SC slipper assist clutch, 6-speed, wet, multi-plate |
| Throttle | Mechanical throttle |
| Top speed | >220km/h |
| Emission | International |

> CHASSIS/SUSPENSION/BRAKES

| | |
|------------------------------|--|
| Frame | Steel tubular frame |
| Swingarm | Aluminum alloy high-arch twin swingarm |
| Rim | Aluminum alloy |
| Front Tire | 120/70 R17 (CST S3N) |
| Rear Tire | 180/55 R17 (CST S3N) |
| Front Suspension | Ø41 inverted suspension, fully adjustable, KYB |
| Rear Suspension | Monoshock rear suspension, adjustable preload & rebound, KYB |
| Front/Rear Suspension Travel | 130mm/130 mm |
| Front Brake | 300mm twin discs, four-piston radial caliper, J.Juan |
| Rear Brake | 240mm single disc, single-piston sliding caliper |
| ABS | Standard |
| Traction Control | Standard, two-level adjustable, switchable |

> DIMENSIONS & WEIGHT

| | |
|--------------------|--|
| LxWxH | 2,020x728x1,105mm |
| Steering Angle | 36° |
| Rake | 23.7° |
| Trail | 93.2mm |
| Wheelbase | 1400mm |
| Seat Height | 810mm (830/795mm with accessory seats) |
| Ground Clearance | 140mm |
| Fuel Tank Capacity | 15L |
| Dry Weight | 175kg |

> ELECTRONICS

| | |
|-----------------------|---------------------|
| Dash | 5-inch TFT display |
| Battery | 12V |
| Day-Running-Light | LED |
| Key | Mechanical key |
| Quickshifter | Upshifting |
| Tire Pressure Monitor | Accessory |
| Headlight | LED animated |
| Taillight | LED |
| Signal Light | LED |
| USB Charge Portal | USB type-A & type-C |
| Action Camera Control | Accessory |
| Steering Stabilizer | Accessory |
| Heated Grips | Accessory |
| OTA Upgrade | Standard |
| APP Connectivity | Standard |
| T-BOX | Optional |

ZHEJIANG CFMOTO POWER CO., LTD.
No. 116, Wuzhou Road, Yuhang Economic Development Zone Hangzhou 311100, Zhejiang Province.

- www.cfmoto.com/global
- @CFMOTOOFFICIAL
- @cfmotoofficial
- CFMOTO
- CFMOTO
- @cfmoto_official

675SR-R

RACING TRIPLE

> DYNAMIC DESIGN

- Aerodynamic bodywork: winglets and brake's air inlets
- Signature led animated lights
- High-arch aluminum swingarm
- Transbody line design element

> TRIPLE-CYLINDER ENGINE

- Sporty exhaust sound
- Low vibrations at high rpm

> SPORT-ORIENTED CHASSIS

- Alloy steel tubular frame
- Front suspension: \varnothing 41mm USD fully adjustable KYB
- rear suspension: monoshock with adjustable preload & rebound KYB
- Front brakes: 300 mm discs, 4-piston calipers, radial brake pump J. Juan
- rear brakes: 240 mm disc, single-piston caliper

> TIME-ATTACK FEATURES

- Quick-shifter, for fast upshifting
- Lap time chrono
- Traction control: 2 levels
- CST S3N dual compound sport tires

> ADVANCED ELECTRONICS

- 5" TFT display
 - Supports various smart features such as My Ride, Real-time location, Reminders, etc. with CFMOTO RIDE APP
- (*The vehicle must be equipped with a T-Box device to enable the above features.)

> RACE-INSPIRED RIDING POSITION

- 15L ergonomic fuel tank
- Tail hump cover with action camera adaptor (Accessory)
- Seat height 810 mm
- (830 / 795 mm with accessory seats)



Aerolite Grey



Nebula Black



Nebula White